



MANY TIRES PLENTY SOLUTIONS



Kerkstraat 90 - 9120 Vrasene - BELGIUM
 Tel. +32-3-755.09.45 - Fax +32-3-755.09.46
 sales@atb.eu www.atb.eu



REM-6



INDUSTRIAL TIRES

Designed for heavy duty applications.
 An excellent tire used on forklift trucks, terminal tractors and other industrial equipment.

- Flat tread pattern for maximum performance
- Exceptional tread wear
- Operations confidence
- Optimal stability



FORKLIFTS



TERMINAL TRACTORS



AIRPORT GROUND SUPPORT EQUIPMENT



REACH STACKER

Tire Size	Load Symbol	Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Rim Width (mm)	Speed	Single Max Load/ Pressure	Load Index
5.00R8	111A5	468	137	24	3.00D	35km/h	1090kg/1000kpa	111
6.00R9	121A5	540	162	25	4.00E	35km/h	1450kg	121
6.50R10	128A5	584	177	27	5.0	35km/h	1800kg	128
7.00R12	136A5	670	190	28	5.00S	35km/h	2240kg	136
225/75R15	149A5	706	230	27	7.0	35km/h	3250kg	149
7.00R15	143A5	736	195	29	5.5	35km/h	2725kg	143
250/70R15	153A5	736	252	28	7.0	35km/h	3650kg	153
315/70R15	165A5	835	312	35	8.0	35km/h	5150kg	165
8.25R15	153A5	838	238	33	6.5	35km/h	3650kg/145psi (steer position) 4750kg/145psi (drive position)	153
10.00R20	166A5	1066	304	35	7.5	35km/h	5288kg	166
12.00R20	176A5	1136	320	40	8.5	35km/h	7100kg	176
12.00R24	178A5	1232	322	39	8.5	35km/h	7500kg	178
14.00R24	193A5	1422	381	63	10.00	35km/h	11200kg	193
18.00R25	207A5	1657	523	63	13.00	35km/h	17000kg	207